

# AWIND BLADES



## HARD MATERIALS

**DESCRIPTION**: A dry cutting blade with continuous turbo rim design that prevents chipping. Special cooling holes. Fast cutting with good life.

USE ME FOR: Indian stone / Granite / Engineering bricks / Clay products Reinforced concrete / Bricks / Concrete products

10MM SEGMENT HEIGHT

**CONTINUOUS TURBO RIM** 

**VENTILATED CORE** 















#### **MATERIAL TYPE**

## HARE MATERIA

GLASS / REINFORCED PLASTIC	
POLYURETHANE	
FIBREGLASS	
MARBLE - DRY CUTTING	
STEEL BARS, PIPE & SECTIONS	
SG & GREY IRON	
PORCELAIN & HARD TILES	
CERAMIC TILES	
INDIAN STONE	
GRANITE	
SLATE	
CLASS A ENGINEERING BRICKS	
CLAY PAVIORS / PIPES / TILES	
FLINT AGGREGATE PRODUCT	
CLASS B ENGINEERING BRICKS	
HEAVILY REINFORCED CONCRETE	
MEDIUM REINFORCED CONCRETE	
LIGHTLY REINFORCED CONCRETE	
CONCRETE	
HARD YORK STONE	
QUARTZITE	
LONDON BRICK	
HARD CONCRETE PRODUCTS	
KERBS / LINTELS / BEAMS	
CAST PIPES	
BRICKS / CONCRETE FLAGS	
HAND MADE BRICKS	
FACING BRICKS	
CONCRETE ROOF TILES	
SOFT CONCRETE PAVIORS	
SAND BASED PAVIORS	
GREEN CONCRETE	
CEMENT SCREED	
LIGHTWEIGHT CONCRETE BLOCK	
HOT ROLLED ASPHALT	
ABRASIVE SAND / GRITSTONE	
ASPHALT OVER CONCRETE	
ASPHALT	
ABRASIVE MORTAR	

HARD MATERIAL & Hard Brick	PLUS
DIMENSIONS	DPH
(4½") 115 x 22.20	115DPH £32.35
(5") 125 x 22.20	125DPH £35.59
(9") 230 x 22.20	230DPH £70.09
(12") 300 x 20.00	300DPH £124.01
(14") 350 x 25.40	350DPH £167.14
(18") 450 x 25.40	450DPH* £267.43

\*450DPH is a 10mm Segmented Narrow Gullet specification

#### CONTINUOUS TURBO RIM


If a diamond blade has a continuous turbo rim then there will be less chipping than with segmented blades and faster cutting due to the castellation of the rim. This clears debris quicker and keeps the blade cool by trapping air in motion.



ORDER LINE: 01909 552470

### **COOLING HOLES**

Cooling holes in a blade as the description says, will keep the steel core cool and will prevent distortion of that core. Keeping the diamond matrix cool in segments will improve speed and life.









NOT SUITABLE