



# MORTAR RAKERS

## DSM



### DSM MORTAR



**DESCRIPTION** : A 6mm thick blade. Good speed of cut and life.

**USE ME FOR** : All types of hard and abrasive mortar.

8MM SEGMENT HEIGHT

STANDARD GULLETS

6MM BLADE WIDTH



#### MATERIAL TYPE

MORTAR RAKING

HARD / DENSE MATERIAL

GLASS / REINFORCED PLASTIC	
POLYURETHANE	
FIBREGLASS	
MARBLE - DRY CUTTING	
STEEL BARS, PIPE & SECTIONS	
SG & GREY IRON	
PORCELAIN & HARD TILES	
CERAMIC TILES	
INDIAN STONE	
GRANITE	
SLATE	
CLASS A ENGINEERING BRICKS	
CLAY PAVIORS / PIPES / TILES	
FLINT AGGREGATE PRODUCT	
CLASS B ENGINEERING BRICKS	
HEAVILY REINFORCED CONCRETE	
MEDIUM REINFORCED CONCRETE	
LIGHTLY REINFORCED CONCRETE	
CONCRETE	
HARD YORK STONE	
QUARTZITE	
LONDON BRICK	
HARD CONCRETE PRODUCTS	
KERBS / LINTELS / BEAMS	
CAST PIPES	
BRICKS / CONCRETE FLAGS	
HAND MADE BRICKS	
FACING BRICKS	
CONCRETE ROOF TILES	
SOFT CONCRETE PAVIORS	
SAND BASED PAVIORS	
GREEN CONCRETE	
CEMENT SCREED	
LIGHTWEIGHT CONCRETE BLOCK	
HOT ROLLED ASPHALT	
ABRASIVE SAND / GRITSTONE	
ASPHALT OVER CONCRETE	
ASPHALT	
ABRASIVE MORTAR	

SOFT / ABRASIVE MATERIAL

#### MORTAR RAKING

BASE

#### DIMENSIONS

DSM

(4 1/2") 115 x 22.2

115DSM £23.72 ∞

(5") 125 x 22.2

125DSM £25.88



THE ENTRY-LINE FROM DURO, WHERE PRICE AND PERFORMANCE ARE MATCHED TO OFFER GREAT VALUE OUTPUT THROUGHOUT THE RANGE.



HIGHLY SUITED   
  NOT SUITABLE  
 SUITABLE WITH RESERVATIONS

ORDER LINE: 01909 552470

WWW.DURO-DIAMONDS.COM