DURO DIAMOND BLADES DUT

DURO ULTRA — DUT PORCELAIN TILE BLADE

DESCRIPTION : Super Thin at 1.4mm thick (115, 125 & 150mm), this blade has a continuous rim and turbo design to cut quickly and not chip the materials. Reinforced flange for stability. For angle grinders and fixed machines

USE ME FOR : Porcelain (grade 5), ceramic, natural stone and other very hard tiles. Can be used dry up to 125mm but water is recommended above this dimension.

- 10MM SEGMENT HEIGHT
- CONTINUOUS TURBO RIM (115 & 125MM)
- VENTILATED CORE & REINFORCED FLANGE*
- CAN BE USED DRY UP TO 125MM
- SUPER THIN 1.4MM UP TO 150MM

RIM DESIGN FOR SIZES OVER 125MM

10mm segment height · long life · FAST cutting · turbo design · self cooling

MATERIAL TYPE

		VACUUM BRAZED TILE CUTTING CURVEX
HARD / DENSE MATERIAL	GLASS / REINFORCED PLASTIC	
	POLYURETHANE	
	FIBREGLASS	
	MARBLE - DRY CUTTING	
	STEEL BARS, PIPE & SECTIONS	
	SG & GREY IRON	
	PORCELAIN & HARD TILES	
	CERAMIC TILES	
	INDIAN STONE	
	GRANITE	
	SLATE	
	CLASS A ENGINEERING BRICKS	
	CLAY PAVIORS / PIPES / TILES	
	FLINT AGGREGATE PRODUCT	
	CLASS B ENGINEERING BRICKS	
	HEAVILY REINFORCED CONCRETE	
	MEDIUM REINFORCED CONCRETE	
	LIGHTLY REINFORCED CONCRETE	
	CONCRETE	
	HARD YORK STONE	
	QUARTZITE	
	LONDON BRICK	
	HARD CONCRETE PRODUCTS	
	KERBS / LINTELS / BEAMS	
	CAST PIPES	
	BRICKS / CONCRETE FLAGS	
	HAND MADE BRICKS	
	FACING BRICKS	
	CONCRETE ROOF TILES	
	SOFT CONCRETE PAVIORS	
	SAND BASED PAVIORS	
	GREEN CONCRETE	
	CEMENT SCREED	
	LIGHTWEIGHT CONCRETE BLOCK	
SOFT / ABRASIVE MATERIAL	HOT ROLLED ASPHALT	
	ABRASIVE SAND / GRITSTONE	
	ASPHALT OVER CONCRETE	
	ASPHALT	
	ABRASIVE MORTAR	

HIGHLY SUITED · NOT SUITABLE · SUITABLE WITH RESERVATIONS

PORCELAIN & CERAMIC TILES	ULTRA
DIMENSIONS	DUT
(4½") 115 X 1.4 X 22.2	115DUT £42.06
(5") 125 X 1.4 X 22.2	125DUT £44.21
(6") 150 X 1.6 X 25.4	150DUT £59.31
(7") 180 X 1.6 X 25.4	180DUT £75.48
(8") 200 X 1.6 X 25.4	200DUT £91.66
(9") 230 X 1.6 X 25.4	230DUT £107.84
(10") 250 X 2.0 X 25.4	250DUT £118.62
(12") 300 X 2.0 X 25.4	300DUT £172.54
(14") 350 X 2.4 X 25.4	350DUT £215.67

REINFORCED FLANGE

A reinforced flange gives the diamond blade more stability under extreme use and keeps the steel core in line, therefore giving a cleaner, straighter cut.

CONTINUOUS TURBO RIM

If a diamond blade has a continuous turbo rim then there will be less chipping than with segmented blades and faster cutting due to the castellation of the rim. This clears debris quicker and keeps the blade cool by trapping air in motion.

THE TOP-LINE FROM DURO, WHERE MAXIMUM PERFORMANCE IS THE ONLY CONSIDERATION DURING THE PRODUCT DESIGN PROCESS. THE VERY BEST QUALITY RAW MATERIALS ARE UTILISED TO ENSURE THE HIGHEST POSSIBLE OUTPUT.

DURO ULTRA

ORDER LINE: 01909 552470 WWW.DURO-DIAMONDS.COM