



DIAMOND CORE DRILL MOTOR

DURO

DD-150-MOTOR FOR CORE DRILLING

TECHNICAL DATA

Max Drill Diameter: 162mmØ
 Input Power: 110V standard (Also available in 240V)
 Dimensions: 437mm x 115mm x 289mm
 No Load Speeds: 930/1520/4270rpm
 Weight: 6.4kg
 Fittings: ½" BSP (F) & 1-¼" UNC (M)
 Decibel Level: 97DbA
 Vibration Level: <1.5m/s²

DESCRIPTION : A powerful, feature packed drill motor for use with wet and dry core drills. For dry drilling please select the AD3-DRY adaptor to enable the use of a dry core drill.

USE ME FOR : Wet and dry drilling - either hand held or used in conjunction with a drill rig such as the DD-150-RIG.



DD-150-MOTOR With Handle In Place For Hand Held Drilling

DD-150-MOTOR With No Handle For Use In DD-150-RIG



1.7KW MOTOR

1.7KW POWER MEANS THE DD-150 CAN BE USED WITH CORES UP TO 162MM DIAMETER. THE CORE DRILL WILL PERFORM MORE EFFECTIVELY - FASTER AND WITH LESS BINDING.

3 SPEED MOTOR

DD-150 CAN BE USED EFFECTIVELY WITH THE FULL RANGE OF DIAMETERS FROM 12MM TO 162MM. HIGHEST RPM SETTING IS 4270 RPM.

60MM COLLAR

THE 60MM COLLAR MEANS THAT A USER CAN MOUNT THE DD-150 ON ANY STANDARD DRILL RIG AND USE IT FOR HAND HELD DRILLING.

DOUBLE THREAD TOOL FIXING

DD-150 CAN ACCOMMODATE ½" BSP (M) & 1-¼" UNC (F) DRILLS THROUGH THE USE OF A DOUBLE THREAD (1-¼" UNC EXTERNAL & ½" BSP INTERNAL)

PISTOL GRIP

THE DD150 HAS A BUILT IN PISTOL GRIP AS OPPOSED TO A D-HANDLE. THIS GIVES THE USER THE ABILITY TO GAIN A SAFER AND MORE CONTROLLED DRILLING POSITION.

2 IN-BUILT SPIRIT LEVELS

ENABLES ACCURATE DRILLING

BUILT IN WATER FEED

WATER FEED CONNECTION TO CONNECT DIRECTLY TO DURO DP-DST-13L WATER TANK

CORE DRILL MOTOR	
DESCRIPTION	DD-150
DURO DRILL MOTOR	DD-150-MOTOR £1400.00



ORDER LINE: 01909 552470

WWW.DURO-DIAMONDS.COM